

www.macis.com.sg

VELOCITY CHECK VALVE

Palm Button

Release

PUSH


Valve Operation

MV1586777H Velocity Manual Check Valve is a 2 – Way control valve, it is to provide positive flow shut off in the event of an abnormal flow thru pressure differential.

To open the valve, manually push the palm button until the pressure equalizes on both sides (Input & Output) and allow the shaft to stay at the in position, as below status table on state 2.

Release the palm button, the spring return valve and the ball check to it position, the pressure flow from OUT port to IN port. Pressure loss in the downstream of the OUT port will causes the valve to trip as status table on state 1. Supply pressure is blocked from entering the OUT port.

This type valve also being use with independent operation system, such as LPO (Line Pressure Operate) systems. They provide both the pressure shut off response and the manual reset feature required by LPO systems.



1 2 PALM BUTTON 114.50MM OUT OUT 117.50MM 4-18NP1 Z.0MM MM00. 99 MM0. 5 ĺΝ IN 3/8-18NP 3/8-18NPT

2 PALM BUTTON 114.50MM OUT OUT 117.50MM 8NP 77.0MM 56.00MM 20.0MM 新聞 ſΝ IN 1/2-14NPT 1/2-14NPT OUT


1

Ordering Ref: MV1586777H-3/8



Specification

opeemeaten		
Control Application	2-Way Normally Closed Velocity Check Valve with Manual Palm Button Type	Distinctions
Exterior Shape	Circular Ø44.00 mm (1 ⁴⁷ / ₆₄ *)	Ordering Ref No: MV 1586777H-3/8
Net Weight	1.0 Kg	
Working Media	Oil	Port Connection Size: IN Port : 3/8"NPT M , OUT Port : ¼" NPT F
Max Working Pressure	3,000 PSI (206.8bar)	
Operating Pressure (Palm Button)	0-3,000PSI(0-206.8bar)	
Temperature Range	- 30°C to 120°C Other Temperature Ranges available. Consult Factory	Ordering Ref No: MV 1586777H-1/2
Material(Valve Body)	316 L	Port Connection Size: IN Port : ½" NPT M , OUT Port : ¼" NPT F
Seal Material	Nitrile Rubber(NBR) Other Seal Material are Available Upon Request	
Material (Palm Button)	Polyamide Other Material are Available Upon Request	
Flow Rate	Cv = 0.35	



** Measurement stated are with tolerance of +/-10%. Optional Parts/Material are available upon request.

MACIS PTE LTD

Blk 3015A Ubi Road 1, #01-02 & #01-06 Kampong Ubi Industrial Estate, Singapore 408705

Email : sales@macis.com.sg, TEL : 65-6749 6011 / 65-6749 7882 FAX : 65-6749 1398