www.macis.com.sg

RELIEF VALVE


Model: MV 9461C-6KL (Pressure Range 1,000-6,000psi)

Descriptions

Relief valves (Pressure Safety Valves) are designed or set to open at a predetermined set pressure to protect other equipment from being subjected to pressures that exceed their design limits.

The pressure media enters the relief valve, turning the spring housing clockwise will increase the relief valve pressure setting. Rotating the spring housing counterclockwise will decrease the relief valve pressure setting. When the set pressure is exceeded, the valve is forced open. They have excellent pressure relief and reset repeatability.


- —Leak tight when 90% of "set pressure" is applied.
- —Repeatability $\pm 5\%$ of "set pressure".
- -Re-seating within 20-30% of "cracking pressure". State details when ordering.



Ordering Ref: MV9461C-6KL-I3/8NPTF-O3/8NPTF

Corresponding to: MV 9462515-3/8-A-L

Ordering Ref: MV9461C-6KL-I1/4NPTF-O1/4NPTF
Corresponding to: MV 9462515-1/4-A-L



Ordering Ref: MV9461C-6KL-I1/2NPTF-O1/2NPTF

Corresponding to: MV 9462515-1/2-A-L

Specification

opcomoditori	
Control Application	2-Way, Two Position Normally Closed, Spring / Poppet Operated Used to control or limit the pressure in a system
Pressure Range	1,000-6,000 PSI (69.0 – 413.7 bar)
Orifice Size	Ø 2.4 mm(³ / ₃₂ ")
Flow Rate	Cv = 0.2
Panel Hole Size	Ø42.5mm (1 ⁴³ / ₆₄ ")
Net Weight	1.1 KG
Working Media	Air
Temperature Range	- 30°C to 120°C Other Temperature Ranges available. Consult Factory
Material(Valve Body)	316 L
Seal Material	Viton(FKM) Other seal material are available upon request
Options	Body Material and end connections other option available upon request

Distinctions

Ordering Ref No: MV 9461C-6KL-I3/8NPTF-O3/8NPTF

Ordering Ref No: MV 9461C-6KL-I1/2NPTF-O1/2NPTF

1

Port Connection Size: IN & OUT Ports: 3/8"-18NPTF F

Port Connection Size: IN & OUT Ports: 1/2"-14NPTF F

Ordering Ref No: MV 9461C-6KL-I1/4NPTF-O1/4NPTF



Port Connection Size : IN & OUT Ports: 1/4"-18NPTF F

^{**} Optional Parts/Material are available upon request.